

PAPER • OPEN ACCESS

Effective use of motor oil resources of the tractor of the company “Claas” in the conditions of Uzbekistan

To cite this article: E Ganiboyeva *et al* 2022 *IOP Conf. Ser.: Earth Environ. Sci.* **1076** 012084

View the [article online](#) for updates and enhancements.



The advertisement is a dark teal banner with white and orange text. On the left, the ECS logo is followed by the text 'The Electrochemical Society Advancing solid state & electrochemical science & technology'. Below this, it says '242nd ECS Meeting' and 'Oct 9 – 13, 2022 • Atlanta, GA, US'. Further down, it mentions 'Early hotel & registration pricing ends September 12' and 'Presenting more than 2,400 technical abstracts in 50 symposia'. On the right side, it lists 'The meeting for industry & researchers in BATTERIES ENERGY TECHNOLOGY SENSORS AND MORE!' and includes a 'Register now!' button with a checkmark icon. Below the text, there are two small images: a portrait of M. Stanley Whittingham and a Nobel Prize medal. To the right of the medal, it says 'ECS Plenary Lecture featuring M. Stanley Whittingham, Binghamton University Nobel Laureate – 2019 Nobel Prize in Chemistry'. On the far right, there are two images: a large audience in a lecture hall and a person pointing at a screen displaying various scientific icons.

ECS The Electrochemical Society
Advancing solid state & electrochemical science & technology

242nd ECS Meeting
Oct 9 – 13, 2022 • Atlanta, GA, US

Early hotel & registration pricing
ends September 12

Presenting more than 2,400
technical abstracts in 50 symposia

The meeting for industry & researchers in
BATTERIES
ENERGY TECHNOLOGY
SENSORS AND MORE!

 **Register now!**

  **ECS Plenary Lecture featuring**
M. Stanley Whittingham,
Binghamton University
Nobel Laureate –
2019 Nobel Prize in Chemistry



Effective use of motor oil resources of the tractor of the company "Claas" in the conditions of Uzbekistan

E Ganiboyeva, B Kh Norov, S Suyunov and I Khudaev

National research university "Tashkent Institute of Irrigation and Agricultural Mechanization Engineers", 39, Street Kari Niyazi, Tashkent, 100000, Uzbekistan

*E-mail ganiboyeva.0804@mail.ru

Annotation: The article describes in detail the reliable operation of modern high-performance and complex "CLAAS" techniques, the correct selection of lubricants and compliance with the optimal operating procedure, as well as the results of the analysis of friction elements of motor oils. It is necessary to compare the quality indicators determined on the basis of research and the concentration of friction elements in the oil with standard values. In order to determine the recommended engine oil change intervals in the engines of CLAAS tractors, it is necessary to determine their quality indicators and the concentration of friction elements in the oil. In order to maintain the performance of the oil, it is recommended to add additives during operation. Study of wear conditions of oils used in internal combustion engines. Determination and justification of the limit working life of oils used in internal combustion engines. Study and justification of properties of interchangeable oils used in internal combustion engines. It is necessary to develop scientific justification and recommendations for increasing the service life of the oils used in internal combustion engines.

1. Introduction

UzCLAAS Agro LLC, which was established on the basis of the decision of the President of the Republic of Uzbekistan dated March 19, 2010 on the establishment of a joint venture for the production of agricultural machinery with the "CLAAS" concern, started production of agricultural tractors in 2010. In 2003, the German "CLAAS" concern bought a 51% stake in the French tractor manufacturing company "Renault Agriculture" (in 2006, the share of the "CLAAS" concern in the "Renault Agriculture" company increased to 80%) and produced tractors under the "CLAAS" sales center. began to issue.

2. Materials and methods

One of the main factors in ensuring the uninterrupted operation, durability and reliability of modern high-performance and sophisticated CLAAS equipment is the correct selection of lubricants and compliance with the optimal operating procedure.

It is known that the climatic conditions of Uzbekistan correspond to the sharply changing continental conditions compared to the American and European climates. This, in turn, is closely related to the oil hydration of internal combustion engines.

The operating conditions of Central Asia affect both the process of natural deterioration of oil quality and the operation of the lubrication system.



shows. As a result, it is necessary to reduce the periodicity of mandatory operations for servicing the lubrication system compared to the standards established for the middle region of our country, to take additional measures to ensure the reliable and long-term operation of the, to reduce the wear of parts and the costs of their repair [1, 2, 3, 4].

The high temperature of the environment and intense solar radiation worsen the cooling of parts and oil, causing their temperature to rise. This condition leads to a decrease in the viscosity of the oil, a decrease in the bearing capacity of the oil layer between the friction surfaces of the crankshaft bearings and other components. All this makes their working conditions close to marginal exploitation.

An increase in air temperature accelerates the oxidation processes in the oil, causing its wear and tear and the effect of its deposits to decrease. Due to sudden changes in air temperature during the day, the amount of water in the oil increases as a result of the conversion of atmospheric air into water in the crankcase wall and parts, which, combined with oxidizing phenomena, leads to an increase in the aggressiveness of the oil and a decrease in the alkali number. It was found that 1% of water in the oil increases the bending of the piston rings by 1.8...2 times. An increase in water in the oil worsens its filterability, reduces the permeability of filters, and creates conditions for malfunctions. In this respect, centrifuges have certain advantages over filters. The formation of water in the oil causes this paper filter to clog and change its structure, resulting in large impurities enters the system and accelerates the bending of engine parts [5, 6, 7, 8].

One of the main characteristics that affect the internal combustion engine lubrication system and engine performance in the climate of the Central Asian region is that the amount of air on the side of the road and in the field is high, and the abrasive properties of dust are high. At a height of 0.65 m above ground level, 66% of the dust consists of small dispersed particles up to 10 μm in size. They enter the engine crankcase through oil filler necks, oil metering holes, and even very small imperfections in the joints of external parts. The smallest dust (up to 3 μm), which is not retained in oil filters, collides with oxidation products and oil polymerization products and forms thin colloidal particles, which can increase the size of dust particles and accelerate friction. In addition, gentle cleaning quickly clogs the holes of the filter, increases their internal resistance, and worsens oil filtration. They get into the gap between the rubbing parts and cause rapid wear of the surfaces. Therefore, it is recommended to use the method of gentle cleaning of the oil in full flow mode with frequent replacement of filter elements [9, 10].

It is necessary to determine the physico-chemical properties of oils and the amount of active elements remaining in its composition, and to add additives for a certain purpose depending on their residual amount and properties. These works, in turn, require theoretical and practical research. The fact that the climate of Uzbekistan is hot and dusty causes the amount of dust in the air to change the quality of the oil. This leads to corrosion of engine parts and an increase in the consumption of fuel and lubricants [11]. Use motor oils wisely

Research work on determining replacement periods is being conducted based on the requirements set by state standards.

According to the conducted studies, during the period of use of motor oils, it is suggested and recommended to add necessary additives in the process of operation in order to restore their performance [11, 12].

It is possible to solve the problem as follows. Agrimot 15W40 motor oils used in the ARION630S tractor were sampled at regular intervals and quality indicators were determined according to state standards. In order to determine the period of reasonable replacement of motor oils, it was found necessary to determine the change in their quality indicators during the period of operation and the concentration of corrosion elements collected in its composition. Research work was carried out in Surkhandarya, Fergana, Tashkent regions.

Table 1. Permissible physical and chemical parameters of motor oils

No	physical and chemical indicators	Amount
1	Change in viscosity at a temperature of 100o C - decrease (on demand)	17,54 12,5

	- increase (on demand)	16,3
	Ignition temperature, max	220
	Total alkaline index, max	6,80
	Diesel fuel in oil, max	
2	Deflection elements, not more than the specified value:	
	- iron (Fe)	100
	- copper(Cu)	30
	- Aluminum(Al)	30
	- lead(Pb)	30
	- chromium (Cr)	20
	- silicon (Si)	35

The amount of elastic elements of motor oils was determined according to GOST 20759-90. The amount of metal contained in the motor oil of the obtained sample was determined by the method of standard-spectral analysis, and the results are presented in tables 2, 3, 4.

3. Results and discussion

Table for determining the amount of friction elements in Agrimot 15W40 motor oil.

Table 2. Surkhandarya region

Sampled, motorcycle watch	The amount of metal in the oil, (mg/kg) , accepted						
	Fe	Pb	Al	Cu	Cr	Si	Sn
	100	30	30	30	20	35	30
50	75,47	3,82	15,79	14,81	4,48	8,15	1,1
100	78,02	3,91	15,84	14,90	4,51	7,54	1,3
150	84,32	4,41	16,77	15,10	5,78	7,79	1,4
200	97,18	4,77	18,12	16,24	6,01	7,97	1,7
220	102,8	4,85	26,45	18,84	7,61	9,54	1,8
250	109,2	5,35	28,86	26,96	9,78	11,06	2,3

Table 3. Fergona region

50	77,16	2,20	15,34	14,60	4,37	8,10	1,0
100	81,10	3,15	16,74	15,44	4,90	8,81	1,67
150	90,7	4,97	18,10	16,78	5,13	8,99	1,78
200	98,0	5,45	19,74	17,20	5,40	9,10	1,97
220	101,6	6,87	25,06	19,37	6,84	10,87	2,13
250	106,2	8,65	28,9	24,45	7,48	12,68	3,19

Table 4. Tashkent region

50	87,10	3,18	20,84	19,06	5,29	9,48	1,26
100	88,11	3,24	21,6	19,14	5,38	9,67	1,33
150	89,24	3,80	21,9	19,37	5,49	9,71	1,40
200	94,56	4,10	24,12	24,7	6,45	10,54	1,56
220	102,1	4,82	26,16	24,7	7,86	12,65	1,70
250	104,5	5,76	28,67	25,34	6,57	11,17	1,90

According to the results of the conducted research, it was observed that the content of Fe-iron element in Agrimot 15W40 motor oil exceeds the limit specified in the GOST requirements when it reaches 220 moto hours. But the amount of other types of metal elements in the oil meets the requirements of GOST.

4. Conclusions

Taking into account the above-mentioned problems, the scientific justification of increasing the efficiency of oils when using promising CLAAS techniques used in the conditions of Uzbekistan is considered

To achieve this goal, it is necessary to solve the following issues:

- The reliable operation of CLAAS machines, increasing the productivity, first of all, is the optimal and correct selection of lubricants for these machines.
- In the climatic conditions of Uzbekistan, the high temperature and large amount of dust particles lead to deterioration of oil quality.
- It is necessary to compare the quality indicators determined on the basis of research and the concentration of friction elements in the oil with standard values.
- In order to determine the recommended engine oil change intervals in the engines of CLAAS tractors, it is necessary to determine their quality indicators and the concentration of friction elements in the oil.
- In order to maintain the performance of the oil, it is recommended to add additives during operation.
- Study of wear conditions of oils used in internal combustion engines.
- Determination and justification of the limit working life of oils used in internal combustion engines.
- Study and justification of properties of interchangeable oils used in internal combustion engines.
- It is necessary to develop scientific justification and recommendations for increasing the service life of the oils used in internal combustion engines.

References

- [1] Sharipov K A New technological principles for the regeneration of spent tractor engine oils in the conditions of the Republic of Uzbekistan. Doctor.dissertation. TADI 2005
- [2] Astanakulov K.D , Rasulov A D, Baimakhanov K A, Eshankulov Kh M and Kurbanov A J 2021 *IOP Conference Series: Earth and Environmental Science* **848 (1)** 012171
- [3] Sattarov N, Borotov A, Ashurov N, Sattarov M, Yunusov R and Abduganiev A 2020 *IOP Conference Series: Earth and Environmental Science* **548** 1-5
- [4] Astanakulov K D, Umirov A T, Sultanbekova P S and Alpamyssova G B 2021 *IOP Conference Series: Earth and Environmental Science* **839 (5)** 052048
- [5] Astanakulov K D, Baimakhanov K A, Alpamyssova G B and Babojanov A B 2021 *IOP Conference Series: Earth and Environmental Science* **839 (5)** 052062
- [6] Astanakulov K D , Balabanov V I, Vitliemov P, Ashurov N A and Khakberdiev O 2021 *IOP Conference Series: Earth and Environmental Science* **868 (1)** 012077
- [7] Karimov M R, Astanakulov K D, Saitov V, Usmanov N K and Israilova D A 2021 *IOP Conference Series: Earth and Environmental Science* **868 (1)** 012050
- [8] Borotov A 2021 *IOP Conference Series: Earth and Environmental Science* **868** 012035
- [9] Ergashxon Ganiboyeva, Jakhongir Rakhmatullayev, Raykhon Sapayeva, Shahzod Jumayev and Abbos Hasanov *Journal of Engineering and Technology (JET)* ISSN(P):2250-2394; ISSN(E): Applied Vol. 12 Issue 2 Dec 2022 17-28
- [10] Khakimov B B, Rajabov N Q, Sharipov Z Sh, Kalandarova S T, G'Aniboyeva E M and Kulmamatov O A 2021 *IOP Conference Series: Earth and Environmental Science*, **868 (1)** 012022
- [11] Borotov A 2020 *IOP Conference Series: Materials Science and Engineering* **883** 012160
- [12] Shaymardanov B, Borotov A and Jumatov Y *IOP Conference Series: Materials Science and Engineering* **883** 2020 Pp 1-9